



System DW-BLACK 50

DESCRIPTION

Black matt powder-coated double wall system made of stainless steel for all standard fireplaces in negative pressure operation, in dry or wet operation

MATERIAL

Inside: L99

Outside: Elo-galvanized

FINISHING

Black powder-coated (RAL 9011 matt roughened)

WALL THICKNESS

Inside / outside each 0.5 mm

INSIDE DIAMETER

130 - 200 mm

INSULATION

Mineral insulation with 25 mm thickness

CONNECTION

Plug connection socket / bead with clamping band

LOCKING BAND

Included

ORDER CODE

The article code for your order results from:

Article code + Ø (Ex: 16-290-DWETN05130). Please refer to the respective code for deviations.



CHARACTERISTICS

- Inexpensive black matt powder-coated exhaust system
- 70 mm wide, recessed locking band
- Resistant to soot fire or moisture

APPLICATION AREAS

- Standard fireplaces for oil, gas and solid fuels (natural wood, coke, peat, coal*)

* excluding anthracite coal from Ibbenbüren, Germany

CE MARK NUMBER

0036 CPR 9174 137

CE CLASSIFICATION ACC. TO DIN EN 1856-1

T450 - N1 - W - V2 - L99050 - G80

CONNECTING PIPE

CE MARK NUMBER

0036 CPR 9174 138

CE-CLASSIFICATION ACC. TO DIN EN 1856-2

T450 - N1 - W - V2 - L99050 - G170 M