



System DW-VISION

DESCRIPTION

The designer chimney: Double wall design chimney system made of stainless steel with a smooth tubular column and without locking bands

MATERIAL

Inside: 1.4404 (316L) / 1.4571 (316Ti)

Outside: 1.4301 (304)

Others on request

FINISHING

Brushed

Highly polished: on request,

Painted: reduced discount (see condition agreement)

(Replacement paint for touch up must be ordered separately:

Code: LACK-DOSE, 18.00 € net per 400 ml can)

WALL THICKNESS

Inside / Outside each 0.6 mm

Others on request

INSIDE DIAMETER

130 - 300 mm

INSULATION

Mineral insulation 32.5 mm thick

CONNECTION


Push-fit connection (outer pipe)

ORDER CODE

The article code for your order results from:

Article code + Ø (Example: DWV262180).

Please refer to the respective code for deviations.



CHARACTERISTICS

- Elegant design with a smooth tubular column and brushed finish
- Cylindrical slip-on connector ends on the outer pipe eliminate the need for locking bands
- Resistant to soot fire or moisture

APPLICATION AREAS

- Standard fireplaces for oil, gas and solid fuels (natural wood, coke, peat, coal *)

* except anthracite coal from Ibbenbüren, Germany

CE MARK NUMBER

0036 CPR 9174 009

CE CLASSIFICATIONS ACC. TO DIN EN 1856 - 1

T600 - N1 - D - V3 - L50050 - G50

T400 - N1 - W - V2 - L50050 - O20

T450 - N1 - W - V2 - L50050 - O50

T600 - N1 - W - V2 - L50050 - G50

CONNECTING PIPE

CE MARK NUMBER

0036 CPR 9174 048

CE CLASSIFICATIONS ACC. TO DIN EN 1856-2

T600 - N1 - D - V3 - L50050 - G100M

T450 - N1 - W - V2 - L50050 - O50M

T600 - N1 - W - V2 - L50050 - G100M