



System PELLET-LINE

DESCRIPTION

Connecting pipe made of stainless steel with internal gasket for connecting to pellet stoves and use as a visible element in living rooms

MATERIAL

Stainless steel 1.4404 (316L)

FINISHING

Heat-resistant silicon paint

Colours:

Unpainted

Black RAL-SI-TS70030020

Cast grey RAL-FEYCOSIL242

WALL THICKNESS

0.4 mm

INSIDE DIAMETER

80 - 100 mm

Others on request

CONNECTION

Push-fit connection retracted with special internal gasket

ORDER CODE

The article code for your order results from:

System + article code + Ø (e.g.: 15-EWPV013080)

If you require a different color, please use instead

15-EWPV (black) the article code 25-EWPV (cast gray)



CHARACTERISTICS

- Resistant to soot fires and moisture
- Pressure tight up to 200 Pa

APPLICATION AREAS

- Connecting pipe to pellet stoves

CE MARK NUMBER

0036 CPR 9174 072

CE CLASSIFICATIONS ACC. TO DIN EN 1856 - 2

Without radiation protection

T200 - N1 - D - V2 - L50040 - G400M (without coating)

T200 - N1 - D - V2 - L50040 - GxxNM (with coating)

T200 - P1 - W - V2 - L50040 - O50M (without coating)

Distances with radiation protection G200

xx = Clearances to flammable materials depend on the diameter, see performance declaration