

System	Oil	Gas	SF	Working temp.	Material	Wall thickness	TIG	Pressure	Certification	Classifications
DW-FU	✓	✓	✓	≤ 400 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	0036 CPR 9174 001	T400 - N1 - D - V3 - L50060 - Gxx T400 - N1 - W - V2 - L50060 - Oxx T600 - N1 - D - V3 - L50060 - Gxx T600 - N1 - W - V2 - L50060 - Oxx
DW-FU Connecting pipe	✓	✓	✓	≤ 450 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	0036 CPR 9174 047	T450 - N1 - W - V2 - L50060 - O50M T600 - N1 - D - V3 - L50060 - G100M T600 - N1 - W - V2 - L50060 - O100M
DW-AL	✓	✓		≤ 120 °C ≤ 200 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	P1 200 Pa	0036 CPR 9174 003	With EPDM -Sealing: T120 - N1 - W - V2 - L50060 - O00 T120 - P1 - W - V2 - L50060 - O00 With Silicone -Sealing: T200 - N1 - W - V2 - L50060 - O00 T200 - P1 - W - V2 - L50060 - O00
DW-AL Connecting pipe	✓	✓		≤ 120 °C ≤ 200 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	P1 200 Pa	0036 CPR 9174 050	With EPDM -Sealing: T120 - P1 - W - V2 - L50060 - O00M T120 - N1 - W - V2 - L50060 - O00M With Silicone -Sealing: T200 - P1 - W - V2 - L50060 - O00M T200 - N1 - W - V2 - L50060 - O00M
DW-SILVER	✓	✓	✓	≤ 600 °C	Inside: 1.4539 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	Z - 7.1 - 3375	T600 - N1 - W2 - G50 - L00
DW-SILVER Connecting pipe	✓	✓	✓	≤ 600 °C	Inside: 1.4539 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	Z - 7.1 - 3375	T600 - N1 - W2 - G100M
DW-ECO 2.0	✓	✓	✓	≤ 400 °C ≤ 600 °C	Inside: L99 Outside: 1.4301	Inside: 0,5 mm Outside: 0,5 mm	✓	N1	0036 CPR 9174 015	T400 - N1 - W - V2 - L99050 - Oxx T600 - N1 - W - V2 - L99050 - Oxx T600 - N1 - W - V2 - L99050 - Gxx
DW-ECO 2.0 Connecting pipe	✓	✓	✓	≤ 450 °C ≤ 600 °C	Inside: L99 Outside: 1.4301	Inside: 0,5 mm Outside: 0,5 mm	✓	N1	0036 CPR 9174 054	T450 - N1 - W - V2 - L99050 - O50M T600 - N1 - W - V2 - L99050 - G100M T600 - N1 - W - V2 - L99050 - O100M
DW-ECO 2.0 AL	✓	✓		≤ 120 °C ≤ 200 °C	Inside: L99 Outside: 1.4301	Inside: 0,5 mm Outside: 0,5 mm	✓	P1 200 Pa	0036 CPR 9174 046	With EPDM -Sealing: T120 - P1 - W - V2 - L99050 - O00 T120 - N1 - W - V2 - L99050 - O00 With Silicone -Sealing: T200 - P1 - W - V2 - L99050 - O00 T200 - N1 - W - V2 - L99050 - O00
DW-ECO 2.0 AL Connecting pipe	✓	✓		≤ 120 °C ≤ 200 °C	Inside: L99 Outside: 1.4301	Inside: 0,5 mm Outside: 0,5 mm	✓	P1 200 Pa	0036 CPR 9174 053	With EPDM -Sealing: T120 - P1 - W - V2 - L99050 - O00M T120 - N1 - W - V2 - L99050 - O00M With Silicone -Sealing: T200 - P1 - W - V2 - L99050 - O00M T200 - N1 - W - V2 - L99050 - O00M
DW-BLACK	✓	✓	✓	≤ 450 °C	Inside: L99 Outside: Elo-galvanized	Inside: 0,5 mm Outside: 0,5 mm	✓	N1 40 Pa	0036 CPR 9174 137	T450 - N1 - W - V2 - L99050 - G80
DW-BLACK Connecting pipe	✓	✓	✓	≤ 450 °C	Inside: L99 Outside: Elo-galvanized	Inside: 0,5 mm Outside: 0,5 mm	✓	N1 40 Pa	0036 CPR 9174 138	T450 - N1 - W - V2 - L99050 - G170 M
DW-KL	✓	✓	✓	≤ 200 °C ≤ 400 °C ≤ 450 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPD 9174 002	T200 - P1 - W - V2 - L50060 - O00 T200 - H1 - W - V2 - L50060 - Oxx T400 - N1 - D - V3 - L50060 - Gxx T400 - N1 - W - V2 - L50060 - Oxx T400 - P1 - W - V2 - L50060 - Oxx T450 - H1 - W - V2 - L50060 - Oxx T600 - N1 - D - V3 - L50060 - Gxx T600 - H1 - W - V2 - L50060 - Gxx
DW-KL Connecting pipe DW-KH	✓	✓	✓	≤ 200 °C ≤ 450 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPR 9174 041	T200 - P1 - W - V2 - L50060 - O00M T200 - H1 - W - V2 - L50060 - O20M T450 - H1 - W - V2 - L50060 - O50M T600 - N1 - D - V3 - L50060 - G100M T600 - H1 - W - V2 - L50060 - G100M
DW-VISION	✓	✓	✓	≤ 400 °C ≤ 450 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	0036 CPR 9174 009	T600 - N1 - D - V3 - L50050 - G50 T400 - N1 - W - V2 - L50050 - O20 T450 - N1 - W - V2 - L50050 - O50
DW-VISION Connecting pipe	✓	✓	✓	≤ 450 °C ≤ 600 °C	Inside: 1.4571/ 1.4404 Outside: 1.4301	Inside: 0,6 mm Outside: 0,6 mm	✓	N1	0036 CPR 9174 048	T600 - N1 - D - V3 - L50050 - G100M T450 - N1 - W - V2 - L50050 - O50M
DW-POWER 32	✓	✓	✓	≤ 600 °C	Inside: 1.4404 Outside: 1.4301	Inside: 0,5 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPR 9174 139	T600 - H1 - D - V2 - L50050 - Oxx
DW-POWER 32 Connecting pipe	✓	✓	✓	≤ 600 °C	Inside: 1.4404 Outside: 1.4301	Inside: 0,5 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPR 9174 166	T600 - H1 - D - V2 - L50050 - O100M
DW-POWER 57	✓	✓	✓	≤ 600 °C	Inside: 1.4404 Outside: 1.4301	Inside: 0,5 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPR 9174 085	T600 - H1 - D - V2 - L50050 - Oxx
DW-POWER 57 Connecting pipe	✓	✓	✓	≤ 600 °C	Inside: 1.4404 Outside: 1.4301	Inside: 0,5 mm Outside: 0,6 mm	✓	H1 5000 Pa	0036 CPR 9174 088	T600 - H1 - D - V2 - L50050 - O100M

xx = The distances from flammable components are dependent on diameter.

We therefore refer you to our declarations of performance and installation instructions available for download on our homepage.

When ordering chimneys without a base (e.g. with pipe bend and support leg or base plate for intermediate support), please note that a locking band must usually be ordered as well.